IN THE CLAIMS:

1. (Currently Amended) An elastic ~~Elastic~~ connection terminal for an electric ~~switch or junction~~ device, said device comprising a conducting part ~~(14)~~ ~~provided~~ located at one end thereof and comprising ~~with~~ a support strip ~~(18)~~ having a front face and a back face comprising~~with~~ a connection region ~~(18c)~~, the terminal for being fastened to the support strip and comprising:

[-] an elastic loop ~~(20) provided with~~ comprising a fitting arm ~~(21)~~, a cable clamping arm ~~(22)~~ and a bent part ~~(23)~~ connecting the fitting arm and the clamping arm, the fitting arm for abutting~~being applied on~~ the front of ~~the~~ a support strip ~~(18)~~ of an electric device ~~to come into~~ and being in contact with ~~the~~ a conducting part ~~(14)~~ of an electric device, ~~while the~~ said clamping arm having ~~is provided with~~ a window ~~arranged to clamp~~ for clamping a cable between the back face of ~~the~~ such support strip and an edge of the window[,] ; and[,]

[-] an auxiliary part ~~(30) capable of forming a stop~~ for stopping one end of ~~the~~ a cable inserted into the terminal,

wherein

[-] the auxiliary part ~~(30)~~ is brought into contact with the back face ~~(18b)~~ of ~~the~~ a support strip of an electric device ~~(18)~~ and ~~is provided with~~ comprises at least one attachment element ~~(34)~~ for gripping a region of ~~the~~ such a support strip ~~(18) so as to be~~, thereby joining ~~joined to the~~ with such a conducting part of an electric device.

2. (Currently Amended) The terminal ~~Terminal~~ according to claim 1, wherein the auxiliary part ~~(30) has~~ comprises cable guide panels ~~(31)~~, the panels for extending as far as ~~the~~ a connection region ~~(18c)~~ of ~~the~~ a support strip of an electric device and comprising attachment elements ~~(34)~~ located adjacent such a ~~near this~~ connection region.

3. (Currently Amended) ~~Terminal~~ The terminal according to claim 2, wherein the auxiliary part ~~(30) has~~ further comprises a back wall, ~~(33) and that~~ wherein the guide panels ~~(31)~~ are for abutting a support strip of an electrical device together with the back wall to define an individual compartment ~~(37)~~ for each cable, ~~with the support strip (18) and the back wall (33), this~~ each compartment being ~~delimited by a panel (31) so that it can be~~electrically isolated from ~~the~~ an adjacent compartment ~~(37)~~.

4. (Currently Amended) The terminal ~~Terminal~~ according to claim 2, wherein the guide panels ~~(31) are shaped to form a guide, and particularly a slope, adapted to the shape of the clamping arm and its pivoting movement~~ each have an end portion having a profile for slidingly receiving the clamping arm.

5. (Currently Amended) ~~Terminal~~ The terminal according to claim 1, wherein ~~the conducting part (14) is provided with a slit (19) and that the bottom of~~ the auxiliary part ~~(30)~~comprises a bottom comprising ~~is provided with~~ an assembly tongue for limiting movement of said elastic loop, ~~that acts as a stop (35), the~~ said tongue for passing through ~~the~~ a slit of such a conducting part of an electric device to project on the front side ~~(18a)~~ of ~~the~~ a support strip ~~(18)~~ of such an electric device.

6. (Currently Amended) ~~Terminal~~ The terminal according to claim 5, wherein the tongue ~~(35) is provided with~~ comprises a click-fit ~~or similar~~ element ~~(36) that helps to hold~~for connecting the auxiliary part ~~(30) assembled~~ to ~~the~~ a conducting part ~~(14)~~ of an electric device.

7. (Currently Amended) The terminal ~~Terminal~~ according to claim 1, ~~wherein~~ further comprising a protective part ~~(40) is housed~~ located in the elastic loop and ~~arranged to limit~~ for limiting bending of the elastic loop, the protective part ~~(40)~~ being independent of the auxiliary part ~~(30)~~.

8. (Currently Amended) The terminal ~~Terminal~~ according to claim 1, wherein the auxiliary part ~~(30) is provided with~~ comprises at least one stop ~~(38)~~ for cooperating with a stop face ~~(12b)~~ of ~~the~~ a housing of an electric device ~~in a direction corresponding to pressure being applied to the elastic loop by a manoeuvring tool or pin~~.